



## SAFETY DATA SHEET

### BOSTIK 9252 PRIMER

#### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME BOSTIK 9252 PRIMER

PRODUCT NO. 36180

SUPPLIER BOSTIK LIMITED  
COMMON ROAD  
STAFFORD  
STAFFORDSHIRE  
ST16 3EH  
+44 1785 272625  
+44 1785 272650 (24 HOUR)  
sds.uk@bostik.com

#### 2 HAZARDS IDENTIFICATION

Highly flammable. Vapours may cause drowsiness and dizziness. Irritating to eyes and skin. May cause sensitisation by skin contact.  
Possible risk of harm to the unborn child. Harmful: danger of serious damage to health by prolonged exposure through inhalation. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
Vapours are heavier than air and can travel long distances to a source of ignition Pilot lights can ignite the vapour

CLASSIFICATION Xn;R48/20. Repr. Cat. 3;R63. Xi;R36/38. R43. F;R11. R52/53, R67.

#### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
2-AMINOETHANOL	205-483-3	141-43-5	< 1%	C;R34 Xn;R20/21/22
BUTANONE	201-159-0	78-93-3	5-10%	F;R11 Xi;R36 R66 R67
ETHYL ACETATE	205-500-4	141-78-6	10-30%	F;R11 Xi;R36 R66 R67
HEPTANE AND ISOMERS			1-5%	Xn;R65. Xi;R38. F;R11. N;R50/53. R67.
METHYLCYCLOHEXANE	203-624-3	108-87-2	1-5%	F;R11 Xn;R65 Xi;R38 R67 N;R51/53
OCTANE & ISOMERS			1-5%	Xn;R65. Xi;R38. R67.
ROSIN	232-475-7	8050-09-7	5-10%	R43
TOLUENE	203-625-9	108-88-3	10-30%	F;R11 Repr. Cat. 3;R63 Xn;R48/20,R65 Xi;R38 R67
XYLENE	215-535-7	1330-20-7	5-10%	R10 Xn;R20/21 Xi;R38

The Full Text for all R-Phrases are Displayed in Section 16

#### 4 FIRST-AID MEASURES

##### INHALATION

Remove victim immediately from source of exposure. Move into fresh air and keep at rest. Get medical attention if any discomfort continues.

##### INGESTION

DO NOT induce vomiting. Get medical attention immediately.

##### SKIN CONTACT

Remove excess material using a paper towel. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

**BOSTIK 9252 PRIMER****EYE CONTACT**

Important! Immediately rinse with water for 15-30 minutes. Get medical attention immediately. Continue to rinse.

**5 FIRE-FIGHTING MEASURES****EXTINGUISHING MEDIA**

Extinguish with foam, carbon dioxide or dry powder.

**6 ACCIDENTAL RELEASE MEASURES****PERSONAL PRECAUTIONS**

Wear protective clothing as described in Section 8 of this safety data sheet.

**ENVIRONMENTAL PRECAUTIONS**

Prevent entry into drains and water courses.

**SPILL CLEAN UP METHODS**

Absorb onto sand, earth or absorbent granules. Pick up with non-sparking tools and place into metal containers with sealable lids. Mark containers with details of hazards and store in designated area ready for disposal.

**7 HANDLING AND STORAGE****USAGE PRECAUTIONS**

Avoid spilling, skin and eye contact. Use explosion proof electric equipment. Static electricity and formation of sparks must be prevented.

**8 EXPOSURE CONTROLS/PERSONAL PROTECTION**

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
2-AMINOETHANOL	WEL	1 ppm(Sk)	2.5 mg/m3(Sk)	3 ppm(Sk)	7.6 mg/m3(Sk)	
BUTANONE	WEL	200 ppm(Sk)	600 mg/m3(Sk)	300 ppm(Sk)	899 mg/m3(Sk)	
ETHYL ACETATE	WEL	200 ppm		400 ppm		
TOLUENE	WEL	50 ppm(Sk)	191 mg/m3(Sk)	100 ppm(Sk)	384 mg/m3(Sk)	
XYLENE	WEL	50 ppm(Sk)	220 mg/m3(Sk)	100 ppm(Sk)	441 mg/m3(Sk)	

WEL = Workplace Exposure Limit.

**INGREDIENT COMMENTS**

WEL = Workplace Exposure Limits

**PROTECTIVE EQUIPMENT****RESPIRATORY EQUIPMENT**

If ventilation is insufficient, suitable respiratory protection must be provided.

**HAND PROTECTION**

Protective gloves must be used if there is a risk of direct contact or splash. Use protective gloves made of: Nitrile.

**EYE PROTECTION**

Wear splash-proof eye goggles to prevent any possibility of eye contact.

**9 PHYSICAL AND CHEMICAL PROPERTIES****APPEARANCE**

Liquid

**BOSTIK 9252 PRIMER**

COLOUR	Lightly coloured.		
ODOUR	Organic solvents.		
SOLUBILITY	Insoluble in water		
RELATIVE DENSITY	0.95 - 0.99	VISCOSITY	600 - 720 mPas
FLASH POINT (°C)	- 10		

**10 STABILITY AND REACTIVITY**

## STABILITY

No particular stability concerns. Avoid: Heat, sparks, flames.

**11 TOXICOLOGICAL INFORMATION**

## GENERAL INFORMATION

Danger of serious damage to health by prolonged exposure.

## INHALATION

May cause irritation to the respiratory system. Vapour may irritate respiratory system or lungs.

## INGESTION

May cause discomfort if swallowed.

## SKIN CONTACT

May cause skin irritation/eczema May cause sensitisation by skin contact.

**12 ECOLOGICAL INFORMATION**

## ECOTOXICITY

The product contains a substance which is harmful to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

**13 DISPOSAL CONSIDERATIONS**

## GENERAL INFORMATION

Waste to be treated as controlled waste. Disposal to licensed waste disposal site in accordance with local Waste Disposal Authority.

**14 TRANSPORT INFORMATION**

UK ROAD CLASS	3		
PROPER SHIPPING NAME	PAINT RELATED MATERIAL		
UN NO. ROAD	1263	UK ROAD PACK GR.	II
ADR CLASS NO.	3	ADR CLASS	Class 3: Flammable liquids.
ADR PACK GROUP	II	TUNNEL RESTRICTION CODE	(D/E)
HAZARD No. (ADR)	33	ADR LABEL NO.	3
HAZCHEM CODE	+3YE	CEFIC TEC(R) NO.	30GF1-I+II, 30GF1-sp
RID CLASS NO.	3	RID PACK GROUP	II
UN NO. SEA	1263	IMDG CLASS	3
IMDG PACK GR.	II	EMS	F-E, S-E
MFAG	See Guide	UN NO. AIR	1263
AIR CLASS	3	AIR PACK GR.	II

**BOSTIK 9252 PRIMER****15 REGULATORY INFORMATION**

## LABELLING



Harmful



Highly Flammable

## CONTAINS

ROSIN

TOLUENE

## RISK PHRASES

R11	Highly flammable.
R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R63	Possible risk of harm to the unborn child.
R67	Vapours may cause drowsiness and dizziness.

## SAFETY PHRASES

S2	Keep out of the reach of children
S9	Keep container in a well-ventilated place.
S13	Keep away from food, drink and animal feeding stuffs.
S16	Keep away from sources of ignition - No smoking.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S46	If swallowed, seek medical advice immediately and show this container or label.
S51	Use only in well-ventilated areas.
S56	Dispose of this material and its container to hazardous or special waste collection point.

## STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations. Control of Substances Hazardous to Health.

## APPROVED CODE OF PRACTICE

Classification and Labelling of Substances and Preparations Dangerous for Supply.

## GUIDANCE NOTES

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

**16 OTHER INFORMATION**

## GENERAL INFORMATION

This product should be used as directed by Bostik Ltd. For further information consult the product data sheet or contact Technical Services.

## INFORMATION SOURCES

This safety data sheet was compiled using current safety information supplied by distributor of raw materials.

## REVISION COMMENTS

This safety data sheet supersedes all previous issues and users are cautioned to ensure that it is current. Destroy all previous data sheets and if in doubt contact Bostik Limited.

## ISSUED BY

Approved LJ

**BOSTIK 9252 PRIMER**

REVISION DATE	July 2009
REV. NO./REPL. SDS GENERATED	9
DATE	April 2003

## RISK PHRASES IN FULL

R10	Flammable.
R11	Highly flammable.
R20/21	Harmful by inhalation and in contact with skin.
R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R34	Causes burns.
R36	Irritating to eyes.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R43	May cause sensitisation by skin contact.
R48/20	Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R63	Possible risk of harm to the unborn child.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.